

Vertical dead end water hammer arrestor

Desbordes.

Technical Data Sheet





socla.com

Description

The Water hammer arrestors 21 BIS EB reduces strongly soften water hammer due to equipment as mixer tap, 1/4 ball valve, solenoid valve...

- No maintenance required : no greasing, no pumping up because no tank to be swelled
- Optimum working around a 3 bars network
- The way of the flow must be respected to take advantage of venturi internal effect, improving efficiency



21 BIS EB

Vertical dead end water hammer arrestor DESBORDES

DN		PFA	Ref.	Weight Kg
33	mm	in bar		
3/4	20	5	149B7245	0,45

Technical features

lectifical features				
Operating temperature	-10 °C at 80 °C			
Permissible operating pressure (PFA) in water	See table above			
Maximum permissible pressure (PS) other mediums	See table above			
Connection	Female, BSP thread			
Mediums	Water			

Nomenclature and materials

N°	Designation	Matériaux	EURO	ANSI
1	Body	Chrome plated Bronze	CuSn5Zn5Pb5-C	ASTM B 505
2	Membrane	NBR polyamide reinforced		
3	Membrane ring	Brass	CuZn39Pb3	ASTM B 124
4	Screw	Stainless steel	X5CrNi18-10	AISI 304
5	Nut	Stainless steel	X5CrNi18-10	AISI 304
6	Spring	Anticorrosive treated steel	VD Cr Si	
7	Сар	Chrome Bronze	CuSn5Zn5Pb5-C	ASTM B 505
8	Screw	Stainless steel	X5CrNi 18-10	AISI 304

Approvals

Application

plumbing installation.


The Water hammer arrestors 21 BIS EB is for domestic

ACS

International construction Standards : Thread connection NF EN ISO 228

Sizing

DN	D		В	ØE
mm	"	mm	mm	mm
20	3/4	20/27	66	59



The descriptions and photographs contained in this product specification sheet are supplied by way of information only and are not binding.

Socla reserves the right to carry out any technical and design improvements to its products without prior notice. Warranty : All sales and contracts for sale are expressly conditioned on the buyer's assent to Socla terms and conditions found on its website at www.socla.com. Socla hereby objects to any term, different from or additional to Socla terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Socla.



Socla sas

365 rue du Lieutenant Putier • 71530 Virey-Le-Grand • France Tel. +33 03 85 97 42 00 • Fax +33 03 85 97 42 42 contact@wattswater.com • www.socla.com ISO 9001 version 2015 / ISO 18001